

BluSDR™ Radio Module

Overview:

As part of the DTC BluSDR™ family of products, BluSDR-6 is designed specifically for size and weight critical UxV applications, and is particularly suitable for small drone platforms operating in short range applications up to 6km in range.

Based around DTC's SOL8SDR (software defined radio) architecture and offering up to full 400mW output power (frequency dependent), BluSDR™-6 includes MANET IP Mesh capability to allow up to 144 nodes in a self-healing network using DTC's industry leading MeshUltra-X™ waveform.

With two USB interfaces capable of supporting USB cameras and headsets as well as Wi-Fi, cellular and Ethernet dongles, BluSDR™-6 can also be connected to a range of host devices using RNDIS Ethernet over USB connectivity.

Features and Benefits:

- 400mW total output power (2x200mW COFDM transceivers - frequency dependent)
- Ideal for short range applications up to 6km
- MeshUltra™ MANET waveforms included to support up to 144 nodes in a self forming self healing Mesh network
- Support for SBUS and MAVLink protocols
- Optional AES128/256 encryption (accredited to FIPS140-2 for MeshUltra™ waveforms)
- USB support for peripherals such as 3G/4G/Wi-Fi dongles
- 128GB built-in storage
- RNDIS support for Ethernet over USB
- Compact packaging with ultra-miniature connectors
- Low power consumption, typically 4W not including camera
- Exceptionally small size and weight
- Available as a core PCB or a boxed module



BluSDR-6



BluSDR-6-B

Product Information:

Product Codes

BluSDR-6-xxxxyy	BluSDR-6 Core PCB
BluSDR-6-xxxxyy-NC	BluSDR-6 Core PCB (no cables)
BluSDR-6-xxxxyy-B	BluSDR-6 Boxed
BluSDR-6-xxxxyy-B-NC	BluSDR-6 Boxed (no cables)

xxxxyy denotes frequency, see over

Product Includes

CA3740	5-way JST to USB-A (f) cable
CA3742	5-way JST to USB micro-B (f) cable
CA4004	4-way Molex to 2-way Micro-Fit (m) power cable
CA4017	2-way Micro-Fit (f) to banana plugs power cable
CA3903 x 2	MMCX (m) to SMA jack (f) cable 200mm

Accessory Options (sold separately)

*ANT1-100150	1dBi omni antenna SMA 1.0-1.5GHz
*ANT2SMA-200250	2dBi omni antenna SMA 2.0-2.5GHz
AP007377	USB-A (m) to USB micro-B (m) cable
CA3752	MMCX (m) to SMA jack (f) cable 100mm
CA4237	MMCX RA (m) to SMA jack (f) cable 200mm
CA3983	5-way JST to USB Ethernet adaptor
CA4005	2-way Micro-Fit to 7.4V slimline battery
CA4006	2-way Micro-Fit to 8.4V 1.3A battery charger
CA4016	2-way Micro-Fit to 12V 2A DC mains adapter
SA4525	Heat sink clamp
†D740-OEM	USB V2.0 to 10/100 Ethernet converter
SOL8SDR-M-CACLAMP-50	Cable clamp for 50mm length BluSDR
SOL8SDR-M-CACLAMP-56	Cable clamp for 56mm length BluSDR

*Two antennas required per module

† See separate datasheet

BluSDR™ Radio Module

Technical Specification:

IO		Physical (Core PCB)	
RF COFDM transceiver 1	MMCX (female 50Ω)	Dimensions (120170/167235/420520)	56mm x 48mm x 7.7mm
RF COFDM transceiver 2	MMCX (female 50Ω)	Weight (120170/167235/420520)	26g approx.
Power input	Molex 4-way 1.25mm	Dimensions (210250)	50mm x 45mm x 7.7mm
USB1 control and download	JST 5-way 1mm	Weight (210250)	24g approx.
USB2 control and download	JST 5-way 1mm		
GPIO	JST 6-way 1mm		

COFDM Transceivers		Physical (Boxed)	
RF power (frequency dependent)	100mW (+20dBm) per output, 200mW total 200mW (+23dBm) per output, 400mW total	Dimensions (120170/167235/420520)	56mm x 54mm x 11mm
Power step	0.25dB incremental control	Weight (120170/167235/420520)	62g approx.
Tuning step	125kHz	Dimensions (210250)	50mm x 54mm x 11mm
Bandwidth	1.25/1.5/1.75/2.5/3.0/3.5/4.0/5.0MHz (MeshUltra-M/-80/-X) 6.0/7.0/8.0/10.0/12.0/14.0/16.0/20.0MHz (MeshUltra-M/-80)	Weight (210250)	60g approx.
Mesh capacity	Up to 87Mbps MeshUltra		
Carrier modulation	BPSK/QPSK/16QAM/64QAM (adaptive)		
FEC rate	FEC1/2, FEC2/3 (adaptive)		
Receive sensitivity	-98dBm (BW 2.5MHz/QPSK 1/2)		

Encryption		Environment	
Standard	DES	Temperature range	-20°C to +50°C with additional cooling
Licensed	*AES128/256 (subject to export control)	Humidity	Less than 85% non-condensing

Power		Frequency Options	
DC input	6V to 18V reverse polarity protected	120170	1.20-1.70GHz 2x100mW
Power consumption (excluding cameras)	3W typical (2x100mW) 4W typical (2x200mW)	167235	1.67-2.35GHz 2x200mW
		210250	2.10-2.50GHz 2x200mW
		420520	4.20-5.20GHz 2x100mW

Storage		License Options	
Medium	Internal microSD 128GB	BluSDR-IAS	Interference Avoidance Scheme for Mesh
		†BluSDR-P2MP	Point-to-Multipoint System for Mesh
		BluSDR-RANGING	Ranging Measurements for BluSDR Radios
		*AES128	AES128 Cryptography Licence
		*AES256	AES256 & AES128 Cryptography Licence

* Accredited to FIPS140-2 for MeshUltra™ waveforms

† Enables split frequency TX/RX operation for special applications. Contact DTC for more information.

Encrypted products are subject to regulatory export controls

For further information contact your Sales Account Manager, one of our Regional Sales Offices, or email solent.info@domotactical.com

AMERICA
T: +1 517 1563 7077

UK
T: +44 1489 566 750

DENMARK
T: +45 8791 8100

UAE
T: +971 0 44 53 72 01

SINGAPORE
T: +65 6339 0508

AUSTRALIA
T: +61 8 8305 0311