

The TITAN Firecomm HUC5-SB

Short Boom Microphone Headset

THE TITAN FIRECOMM HUC5-SB

The innovate microphone technology used with the Titan Firecomm HUC5-SB headset lets users communicate clearly without needing to have the microphone in front of the mouth.

The microphone sensitivity has been adapted so users can transmit clear audio even when wearing masks and in noisy environments.

The HUC5-SB also has a high-performing speaker, a flame retardant coiled cable and comes with a nexus TP120 connector that fits Titan's portfolio of Remote Speaker Microphones and PTT-units.



Part number:

Right: HUC5-SB-R-TP-C-01

Left: HUC5-SB-L-TP-C-01

Technical data

Loudspeaker specifications		Cable	
Normal size	40mm, 1,5 inch.	Type	Coiled flame retardant UL94 V0
Resonant frequency	530 Hz ± 150 Hz at 1 V	Connector	Nexus TP120 connector
Impedance	8 Ohm ± 15% at 1 KHz 1 V	Microphone	
Sound pressure level	90 dB/w ± 3 dB 0.5 w 50 cm ave at 0.8K, 1K, 1.2K, 1.5K Hz	Type	Omni-directional
Response	Fo Hz ~ 6 KHz max 10 dB	IP-rating	IP67
Input power	Nominal 0.5 W - Handling capacity 1.0 W		